## -: References:-


**1:** Hoffman A.A., Dias S.L.P., Rodrigues J.R., (2008) Methylene blue immobilized on cellulose acetate with titanium dioxide, an application as sensor for ascorbic acid,*J. Braz. Chem. Soc.***19**, 943–949.

**2:** FlorouA.B., ProdromidisM.I., KarayannisM.I., Tzouwara-KarayanniS.M., (2000) Flow electrochemical determination of ascorbic acid in real samples using a glassy carbon electrode modified with a cellulose acetate film bearing 2,6-dichlorophenolindophenol, *Anal. Chim. Acta***409**, 113–121.

**3:** CambrosioA., Limoges C., CourtialJ.P., LavilleF., (1993) Historicalscientometrics? Mapping over 70 years of biological safety research with coword analysis,Scientometrics**27**, 119–143.

**4:** Malhotra B.D., ChaubeyA., Singh S.P., (2006) Prospects of conducting polymers in biosensors, *Anal. Chim.Acta***578**, 59–74.

**5:** ChetnaDhanda,b, SinghaS.P., Sunil K. Aryaa,b, Monika Dattab, Malhotraa,B.D. (2007)analyticachimicaacta**602**, 244–251

**6:** Céspedes, E. Martínes-Fábregas, S. Alegret, (1996) New materials for electrochemical sensing. 1. Rigid conducting composites, *Trends Anal. Chem*. **15**, 296–304.

**7:** ChenJ. ,BurrelA.K. , Collis G.E., OfficerD.L. , Swiegers G.F(2002)ElectrochimicaActa**47,** 2715_ 2724

**8:** AlbertúsF., LlerenaA., AlpízarJ., CerdáV., LuqueM., Ríos A., ValcárcelM., (1997) A PVCgraphite composite electrode for electroanalytical use. Preparation and some applications, *Anal. Chim. Acta***355**, 23–32.

**9:** GhamoussF., .LedruS, RouilléN., LantierF., BoujtitaM., (2006) Bulk modified screenprinting carbon electrodes with both lactate oxidase (LOD) and horseradish peroxidase (HRP) for the determination of L-lactate in flow injection analysis mode, *Anal. Chim.Acta***570**, 158–164.

**10:** Guzman-Vázquez de Prada, Peña N., ParradoC., ReviejoA.J., PingarrónJ.M. (2006) Amperometricmultidetection with composite enzyme electrodes, *Talanta***62**, 896–903.


.

**11:** Cristina García-Aljaroa,1, Mangesh A. Bangarb, Eva Baldrichа(2010) Biosensors and Bioelectronics **25**, 2309–2312

**12:** Jurevičiūtė, K. Brazdžiuvienė, L. Bernotaitė, B. Šalkus, (2005) Polyaniline-modified electrode as an amperometricascorbate sensor, Sens. Actuators, B **107**, 716–721.

**13:** Pavlushkina.,Gladushk S.A., (2000) Synthesis and characterization of sodium borophosphate.*Stekio I keramik***6,** 16-18.
screenprinted electrochemical sensors for biomedical, environmental and industrial analysis, *Trends Anal. Chem.***16**, 89–103.

**14:**Husan M.S, Ahmed.I, Parsons.A.J,(2012) Material Charactrisaton and cytocompatibility Phosphate glass.*J. Mater Sci***23**, 2531-2541.

**15:**. Park J, Kim H.K., Son Y., (2008) Glucose biosensor constructed from capped conducting microtubules of PEDOT, Sens. *Actuators B***133**, 244–250.

**16:**OLEKSEYUK1,I.D. Yu.M. KOGUT1*, YURCHENKO1O.M., PARASYUK O.V. 1, VOLKOV2S.V., (2009), Chemistry of metals and alloys **2,** 49-54.

**17:**KalcherK., Kauffmann J.M., Wang J., SvankaraI., VytrasK., NeuholdC., YangSensors Z. (1995) based on carbon-paste in electrochemical analysis – a review with particular emphasis on the period 1990–1993, Electroanalysis**7** 5– 22.

**18:**Ryszard J, Barczynski (2005) Technical Physics ,*OpticaApplicata***4**, 80-952.

**19**: shah K. V., GoswamiM., DeoM. N., SarkarA., ManikandanS., ShrikhandeV. K. & KothiyalG. P., (2006**)**Bult. Mater Sci. Vol. 29, No.1, 43-48

**20:**Zhu L., TianC., Zhu D., Yang R., (2008) Ordered mesoporous carbon paste electrodes forelectrochemical sensing and biosensing, Electroanalysis**20**, 1128–1134.

**21:**TarsikkP.S ,Sing.B (2009). Asial Journal of chemistry, vol 21 **10,** 162-166,

**22:**SINGHB 1, TARSIKKA P S , SINGH L(2002) Journal of pysicsvol 59 **4**, 653-661.

**23:**Minakshi, PundirC.S., (2008) Construction of an amperometric sensor for triglyceride determination, *Sens. Actuators, B, Chem*. **133,** 251–255.

**24:**ProdromidisM.I., M.I., (2002) Enzyme based amperometric biosensors for food

analysis, Electroanalysis**14**,241–261.

**25:**LuqueM., Ríos A., ValcárcelM., (1999) A poly(vinyl chloride) graphite composite electrode for flow-injection amperometric determination of antioxidants, **395**,217–223.

**26:**Rahman M.M., Muhammad ShiddikyJ.A. , AminurRahmanMd., Yoon-Bo Shim(2009) Analytical Biochemistry **384**,159–165

**27:**Cano M., Ávila J.L., MayénM., Mena M.L., PingarrónJ., Rodrígez-Amaro, R. (2008) A new,third generation, PVC/TTF-TCNQ composite amperometric biosensor for glucose determination, *J. Electroanal. Chem*. **615**, 69–74.

**28:**BarsanM.M., Pinto E.M., FlorescuM., Brett C.M.A.,(2009) Development and characterization of a new conducting carbon composite electrode, *Anal. Chim.Acta* **635**, 71–78.

**29:**Fatma Bilge Emrea,b, FulyaEkizc, AbidinBalana,d, SinanEmree, SunaTimurf,(2011) Sensors and Actuators B **158,** 117– 123.

**30:**GhicaM.E., Brett C.M.A., (2006) Development of novel glucose and pyruvate biosenso poly(neutral red) modified carbon film electrodes. Application to natural samples,Electroanalysis**18**, 748–756.

**31:**Gerard M., ChaubeyA., Malhotra B.D., (2002) Application of conducting polymers to biosensors, Biosens. Bioelectron.**17,** 345–359.

**32:**Aguilar R., DávilaM.M., ElizaldeM.P., MattuschM., WennrichR., (2004) Capability of a carbon-polyvinylchloride composite electrode for the detection of acid and uric acid, *Electrochim. Acta***49** , 851–859

**33:**PauliukaiteR., GhicaM.E., Brett C.M.A., (2005) A new, improved sensor for asco determination at copper hexacyanoferrate modified carbon film electrodes, *Anal.Bioanal. Chem*. **381**, 972–978.

**34:**PauliukaiteR., GhicaM.E., BarsanM., (2007)Characterisation of poly(neutral red) modified carbon film electrodes; application as a redox mediator for biosensors,*J. Solid State Electrochem*.**11**, 899–908.

**35:**Ramirez-Garcia S., AlegretS., CespedesF., Forster R.J., (2002) Carbon compositeelectrodes: surface and electrochemical properties, Analyst **127**, 1512–1519.

**36:**AlegretS., CéspedesF., Martínez-FàbregasE., MartorellD., Morales A., (1996) Carbonpolymerbiocomposites for amperometric sensing, Biosens.Bioelectron. 35-44.

**37:**Miserere S., LedruS., RuilléN., GriveauS., BoujtitaM., BediouiF., (2006) Biocompatible carbon-based screen-printed electrodes for the electrochemical Electrochem.*Commun.* **8,** 238–244.

**38:**LedruS., RouilléN., BoujtitaM., (2006) One step screen-printed electrode modified in bulk with HRP based on direct electron transfer for hydrogen peroxide detection in flow injection mode, Biosens. Bioelectron.**21**,1591–1598.

**39:**Wring S.A., Hart J.P., (1990) Voltammetric behaviour of ascorbic-acid at a graphite epoxy composite electrode chemically modified with cobalt phthalocyanine amperometric determination multivitamin preparation,. *Chim.Acta***229**, 63–70.

**40**: Chanshetti1U. B., Shelke2V. A., Jadhav2S. M., Shankarwar2S.G., Chondhekar2T. K. , Shankarwar3A. Sudarsan4G., V.,Jogad5M. S. J.Physics, Chemistry and Technology Vol. 9, No 1, 2011, pp. 29 – 36 DOI: 10.2298/FUPCT1101029C

**41:**ShrikhandeV. K., MirzaT., KothiyalG. P., MutheK. P., SawantB. B., P. V. Ravindranand SahruV. C., **(1998)** Ind. J. of Pure & Appl. Phys. 36 449).

**42**: Valle.M, Merkoci.A (2005) Sensors and Actuators B **107,** 742-748**.**